



HOT TAPPING E1448 EQB-SS HIGH PRESSURE - SUBSEA MACHINE



SPECIFICATIONS

| Boring Travel | |
|------------------------------|-------------------------------|
| Tapping Size Range | |
| MAOP | 2220 psig @ 100° F |
| Max. Standard Operating Temp | |
| Power Options | -/-/// Hydraulic |
| Auto Feed Rate | 0.004"/Rev. |
| Total Weight | -/- 1095 Kg, 1323 Kg, 1550 Kg |
| Max. Depth Work | 200ft 60mts |

E1448-EQB Tapping Machine providing a tapping Size Range of 14" - 48" with a Boring Bar Travel of 80, 110 and 120 inches EQB-E1448 Tapping Machine has 6"-900# RTJ mounting flange as standard. 600# RTJ front flange is also available The machine is hydraulically powered, via Diesel Hydraulic Power Unit. ENR EQB-E1448 Tapping Machines is capable of operating up to 2200 psig, so allowing safe operations on linesup to full ANSI 900 Operating Pressures The Machine is operated via Tandem Hydraulic Motor with two speed operation on constant flow input, providing Speed Control Features for Cutter Rotation while a separate Hydraulic Motor provides Power Extension and Retraction of the Boring Bar.